

Mac

Compatible products

A-H01, UD-H01, NP-H750, AI-501DA

System requirements

Mac with Intel processor

The following Mac OS versions are supported (as of January 2018)

Mac OS X (Snow Leopard) 10.6.4 or later

OS X Lion (10.7)

OS X Mountain Lion (10.8)

OS X Mavericks (10.9)

OS X Yosemite (10.10)

OS X El Capitan (10.11)

macOS Sierra (10.12)

macOS High Sierra (10.13)

Installing the driver

1 Go to the download page of your product on the TEAC Global web site (<https://teac.jp/jp/language>), and download the Mac Driver.


2 Unzip the downloaded file, then open "TEAC USB HS Audio KEXT Install Package xxxxx.pkg" (xxxxx is the driver version) in the extracted folder.



Note A warning window that says "TEAC USB HS Audio KEXT Install Package xxxx cannot be opened because it is from an unidentified developer." may appear. If it appears, hold the Control key and right click, then choose "Open" from the menu, and click "Open" to continue with the installation.




3 Follow the instructions to proceed with the installation. Your user name and password will be required to proceed with the installation.




Note The user name and password required in this step are those which you use when you start up or log in to the Mac.

4 Choose "Restart" when the installation completes.



In this step, the following message may appear. If it appears, click "OK" to restart.




If you are installing the driver on a system that uses macOS High Sierra, follow steps 5 to 7, otherwise, jump to step 8.

5 After restart, open "Security and Privacy" in System Preferences.



6 Click "Allow" in the "General" tab.

If "Allow" is disabled and grayed out, click the Lock icon [🔒] to allow the setting to be changed.




You can then enter the password you used in step 3.

If the blocked driver is TEAC USB HS Audio alone, it shows "Legacy Developer: Teac".

Important This setting change **MUST** be carried out within 30 minutes of the driver being installed.

Installing the driver (continued from page 1)

7 Click "OK" after checking the box "Legacy Developer: Teac"




The following steps apply to all versions of compatible OS.

8 Connect the TEAC product to the Mac via a USB cable, then click "Sound" in System Preferences.



9 Select "TEAC USB HS ASYNC AUDIO DEVICE" in the "Output" tab.



The installation is now completed.


Note To check the driver was properly recognized by the computer, follow the steps in the following section.

Confirming the driver has been correctly installed

Follow the below steps to confirm the driver is properly recognized by the computer.


1 Play back some music using iTunes or another music application. The driver is recognized by the computer in this step.

2 Double click "System Info" in "Applications" > "Utilities" in the finder menu.



3 Click the "System Extensions" in the "Software" tab, and check "TEAC USB Audio".

If it shows "Loaded: Yes", the computer is correctly recognizing the driver.



Note If it shows "Loaded: No" and random noise is heard from the speakers/headphones, restart the computer and go through the above steps again. If it still says "No", please install the driver again.